

THE USA



### MADE IN

## PRODUCT DATA SHEET

# ACRYLIC ROOF COATING

#### • DESCRIPTION

EZ On Coat<sup>®</sup> Acrylic Roof Coating is an acrylic elastomeric polymer fortified with fibers. It dries by evaporation to yield a non-yellowing, water-repellent surface. EZ On Coat<sup>®</sup> Acrylic Roof Coating is UV stable, and has exceptional abrasion resistance. A sustainable cool roof coating.

#### RECOMMENDED USES

EZ On Coat<sup>®</sup> Acrylic Roof Coating can be applied to surfaces such as metal, masonry, wood, and over EZ On Coat<sup>®</sup> primers after following preparation procedures.

#### APPLICATION

Surface to be treated must be clean. If necessary, remove all dust, grease and loose debris before applying this product. Apply with a brush, roller, or sprayer at a rate of 1.00 gallon per 100 square feet per pass. Multiple passes may be applied at 1 gallon per 100 square feet.

#### BENEFITS

Mildew Resistant Flexible Non-Yellowing Energy Saving Waterproof Non-Toxic Easy Clean Up Abrasion Resistant Prevents Rust

#### • TECHNICAL DATA

| I CHINICAL DATA    |   |
|--------------------|---|
| EMITTANCE:         | 90 ASTM C-1371  |
| REFLECTANCE:       | .78%  |
| FLEXIBILITY:       | Passed 180° Mandrel Bend Test<br>ASTM D-822             |
| VISCOSITY:         | 6,000 – 9,000 cps                                       |
| WEATHERABILITY:    | Passed 4000 Hours ATSM G-53                             |
| FIRE RESISTANCE:   | Class "A" in Assembly                                   |
| FUNGAL RESISTANCE: | Passed ASTM D-3273-73T                                  |
| ELONGATION:        | 300% at 70° F ASTM 2370                                 |
| CLEAN UP:          | Biodegradable citrus cleaning product or soap and water |
| TENSILE:           | 380 psi ASTM D-1653A                                    |
| PERMEABILITY:      | 1.8 perms ASTM D-1653A                                  |
| SOLIDS BY WEIGHT:  | 60% +/- 2% ASTM D-1644                                  |
| SOLIDS BY VOLUME:  | 52% +/- 2% ASTM D-2697                                  |
| VOC:               | <50 grams per liter                                     |
| WEIGHT:            | 11.67 lbs. per gallon +/- 5%                            |

# CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.

 Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

#### CONSULT TECHNICAL DEPARTMENT FOR ANSWERS TO ANY QUESTIONS REGARDING USE OF THIS PRODUCT

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ On Coat\* assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ ON Coat\*, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.