



MADE IN  THE USA

PRODUCT DATA SHEET

SEAM TAPE

DESCRIPTION

EZ On Coat® self-adhering Seam Tape is a butyl rubber with polyester backing. Seam Tape is an instant rubberized water proofing product. It has excellent adhesion.

RECOMMENDED USES

Use EZ On Coat® Seam Tape for sealing seams, flashings and penetrations on metal, EPDM, TPO, PVC, single-ply roofs and all smooth Bitumen and BUR materials.

APPLICATION

Surfaces to receive EZ On Coat® Seam Tape must be clean, dry and sound. Apply by removing the clear release film from the backside and press the Seam Tape firmly into place. Begin by only peeling a few inches off of the tape roll and align tape on the area that will receive the tape. Slowly peel and press tape into place. Overlap the end of the roll by 2 inches. Do not stretch the tape while rolling it out. Allow slack for configuration profiles and coat over the top with EZ On Coat® products as soon as the weather permits.

BENEFITS

- Immediate Water Proofing
- Bridges Gaps
- Odorless
- User Friendly

TECHNICAL DATA

ROLL SIZE:	2" by 50' 4" by 50' 6" by 50'
THICKNESS:	25 mils minimum
BOND TIME:	Immediate
BOND SET:	24 Hours
APPLICATION TEMP:	50° F - 100° F
WIND MOVEMENT:	>15
SERVICE RANGES:	-20° F to 200° F
TENSILE:	790 PSI average
PEEL:	17 lbs. per linear inch
SHELF-LIFE:	Up to 24 months
WATER RESISTANCE:	Excellent
VOC/VOS:	0 grams per liter Free of solvents and asphalts
CLEAN-UP:	Biodegradable Citrus Cleaning Products or oil-based products

CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

CONSULT TECHNICAL DEPARTMENT FOR ANSWERS TO ANY QUESTIONS REGARDING USE OF THIS PRODUCT

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ On Coat® assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ On Coat®, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.