



MADE IN  THE USA

• PRODUCT DATA SHEET

EZ ON COAT RV SEAM-TAPE

• DESCRIPTION

ARC's self-adhering Butyl Tape is a butyl rubber with polyester backing. Butyl Tape is an instant rubberized water proofing product. It has excellent adhesion.

• RECOMMENDED USES

Use ARC's Butyl Tape for sealing seams, flashings and penetrations on metal, EPDM, TPO, PVC, single-ply roofs and all smooth Bitumen and BUR materials.

• APPLICATION

Surfaces to receive ARC's Butyl Tape must be clean, dry, and sound. Apply by removing the clear release film from the back side and press Butyl Tape firmly into place. Begin by only peeling a few inches off of tape roll and align tape on the area that will receive the tape. Slowly peel and press tape into place. Overlap the end of the roll by 2 inches. Do not stretch the tape while rolling it out. Allow slack for configuration profiles and coat over the top with ARC products as soon as the weather permits.

• BENEFITS

- Immediate Water Proofing
- Bridges Gaps
- Odorless
- User Friendly

• TECHNICAL DATA

ROLL SIZE:	2" x 50' 4" x 50' 6" x 50'
THICKNESS:	25 mils minimum
BOND TIME:	Immediate
BOND SET:	24 Hours
APPLICATION TEMP:	40° F - 100° F
WIND MOVEMENT:	>15
SERVICE RANGES:	-20° F to 200° F
TENSILE:	790 PSI average
PEEL:	17 lbs. per linear inch
SHELF LIFE:	Up to 24 months
WATER RESISTANCE:	Excellent
VOC/VOS:	0 grams per liter Free of solvents and asphalts
CLEAN-UP:	Biodegradable citrus cleaning products or ARC's Cleaning Solution for oil-based products

Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

**CONSULT ARC TECHNICAL DEPARTMENT FOR
ANSWERS TO ANY QUESTIONS REGARDING
USE OF THIS PRODUCT**

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ On Coat® assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ On Coat®, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.